

# TPE3005 SERIES

## 0.6WEI30-51 - 50/60Hz PCB Mount Transformer



### FEATURES

- Vacuum filling
- Two compartments bobbins
- Self-extinguishing plastics UL94V0
- Degree of protection IP00
- 40 grams weight

### OPTIONS

- Bulk packaging is standard
- Custom design available

### APPLICATIONS

- Medical equipments
- Industrial equipments
- Industrial controls
- Test equipment
- Industrial computers
- Avionics & telecom

PRIMARY VOLTAGE: 230					
Part Nuber	Secondary V	Secondary mA	No-load V	Amb. Temp.	Rating VA
TPE300513	6	100	9,94	T70B	0,6
TPE300514	9	66	14,95	T70B	0,6
TPE300515	12	50	19,9	T70B	0,6
TPE300516	15	40	24,9	T70B	0,6
TPE300517	18	33	29,9	T70B	0,6
TPE300518	24	25	39,8	T70B	0,6
TPE300519	2 x 6	2 x 50	2 x 9.94	T70B	0,6
TPE300520	2 x 9	2 x 33	2 x 14.95	T70B	0,6
TPE300521	2 x 12	2 x 25	2 x 19.9	T70B	0,6
TPE300522*	2 x 15	2 x 20	2 x 24.9	T70B	0,6
TPE300523*	2 x 18	2 x 17	2 x 29.9	T70B	0,6
TPE300524*	2 x 24	2 x 12	2 x 39.8	T70B	0,6

PRIMARY VOLTAGE: 115					
Part Nuber	Secondary V	Secondary mA	No-load V	Amb. Temp.	Rating VA
TPE300525	6	100	9,94	T70B	0,6
TPE300526	9	66	14,95	T70B	0,6
TPE300527	12	50	19,9	T70B	0,6
TPE300528	15	40	24,9	T70B	0,6
TPE300529	18	33	29,9	T70B	0,6
TPE300530	24	25	39,8	T70B	0,6
TPE300531	2 x 6	2 x 50	2 x 9.94	T70B	0,6
TPE300532	2 x 9	2 x 33	2 x 14.95	T70B	0,6
TPE300533	2 x 12	2 x 25	2 x 19.9	T70B	0,6
TPE300534	2 x 15	2 x 20	2 x 24.9	T70B	0,6
TPE300535	2 x 18	2 x 17	2 x 29.9	T70B	0,6
TPE300536	2 x 24	2 x 12	2 x 39.8	T70B	0,6

- Resin class B CEI 85 (20000 h testing to CEI 126)
- Inherently short-circuits proof transformer
- UL approved primary versions: 24V, 48V, 240V (production on request)

- Insulation voltage 4 KV
- 100% tested production
- Certification : CCA procedure on request

